

|                    |                                                                                                                                                                                           |                                |         |
|--------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------|---------|
| <b>Make</b>        | <b>ARBURG A 375 V 500-170 (only for production cell !)</b>                                                                                                                                |                                |         |
| ID                 |                                                                                                                                                                                           | 3641                           |         |
| Year               |                                                                                                                                                                                           | 2018                           |         |
| Machine-no.        |                                                                                                                                                                                           | 247863                         |         |
| Operating hours    | hrs                                                                                                                                                                                       | 10.000                         |         |
| Screw              | mm                                                                                                                                                                                        | 30                             |         |
| Injection pressure | bar                                                                                                                                                                                       | 2000                           |         |
| Injection volume   | ccm                                                                                                                                                                                       | 85                             |         |
| Clamping force     | t                                                                                                                                                                                         | 50                             |         |
| Tiebare distance   | mm                                                                                                                                                                                        |                                |         |
| Mouldheight        | mm                                                                                                                                                                                        | 200                            |         |
| Daylight max.      | mm                                                                                                                                                                                        | 550                            |         |
| Size + Weight      | mm                                                                                                                                                                                        | 2600 x 1600 x 2300 (transport) | 3200 kg |
| Power              | kW                                                                                                                                                                                        | 11                             |         |
| Description        | Machine without safety-hood only for use in a production cell. A conversion for individual operation with CE certification is uneconomical., Corepuller, Robot Interface, Airvalve etc... |                                |         |







